

## AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

### Listing of Claims:

1           1.       (Currently amended) A method that facilitates dynamic delivery of  
2       service profiles to a client, comprising:  
3           performing a discovery operation to allow the client to discover new  
4       services on a network;  
5           if a new service is discovered for which the client does not possess a  
6       service profile for the new service, causing the client to obtain the service profile  
7       from a service provider of the new service;  
8           wherein causing the client to obtain the service profile involves:  
9           causing the client to send a request for the service profile to the  
10          service provider of the new service, wherein the request includes type  
11          information identifying the type of device platform of the client; and  
12          causing the service provider new service to select the service  
13          profile from a set of service profiles based on the received type  
14          information of the client; and  
15          causing the service profile to be installed on the client to enable the client  
16       to use the new service,  
17          wherein the service profile includes a specification that describes how to  
18       use the new service, and wherein causing the service profile to be installed on the  
19       client involves,  
20          causing device-specific code to be generated to implement the  
21          specification, and

22 causing the code to be installed on the client.

1           2.     (Currently amended) The method of claim 1, wherein causing the  
2 client to obtain the service profile involves:  
3           causing the client to send a request for the service profile to the service  
4 provider of the new service; and  
5           causing the client to receive the service profile from the service provider  
6 of the new service.

1           3.     (Original) The method of claim 1, wherein the service profile  
2 includes code, and wherein causing the service profile to be installed on the client  
3 involves causing the code to be installed on the client.

1           4.     (Cancelled)

1           5.     (Original) The method of claim 1, wherein the service profile is  
2 encoded in a universal form that can be executed by different types of clients.

1           6.     (Currently amended) The method of claim 1,  
2 wherein there exist different service profile implementations for different  
3 types of clients; and  
4           wherein causing the client to obtain the service profile involves,  
5                 communicating characteristics of the client to the service  
6 provider of the new service,  
7                 allowing the service provider of the new service to select a  
8 service profile implementation for the client based on the  
9 characteristics of the client, and

10                               allowing the service provider of the new service to send the  
11                               selected service profile implementation to the client.

1               7.       (Currently amended) The method of claim 1, wherein causing the  
2       client to obtain the service profile from the service provider of the new service  
3       involves executing a dynamic extension profile, which implements a standard  
4       protocol that enables the client to acquire any profile the client needs at the time  
5       the profile is needed.

1               8.       (Currently amended) The method of claim 1,  
2       wherein performing the discovery operation involves using the Bluetooth  
3       Service Discovery Protocol (SDP); and  
4       wherein the client and the service provider of the new service  
5       communicate using the Bluetooth networking standard.

1               9.       (Original) The method of claim 1, wherein the service profile can  
2       define a service-specific Application Programming Interface (API).

1               10.      (Original) The method of claim 1, wherein the service profile  
2       implements a domain-specific protocol stack associated with the new service.

1               11.      (Currently amended) A computer-readable storage medium storing  
2       instructions that when executed by a computer cause the computer to perform a  
3       method that facilitates dynamic delivery of service profiles to a client, the method  
4       comprising:  
5               performing a discovery operation to allow the client to discover new  
6       services on a network;

7 if a new service is discovered for which the client does not possess a  
8 service profile for the new service, causing the client to obtain the service profile  
9 from a service provider of the new service;

10 wherein causing the client to obtain the service profile involves:

11 causing the client to send a request for the service profile to the  
12 service provider of the new service, wherein the request includes type  
13 information identifying the type of device platform of the client; and

14 causing the service provider ~~new service~~ to select the service  
15 profile from a set of service profiles based on the received type  
16 information of the client; and

17 causing the service profile to be installed on the client to enable the client  
18 to use the new service,

19 wherein the service profile includes a specification that describes how to  
20 use the new service, and wherein causing the service profile to be installed on the  
21 client involves,

22 causing device-specific code to be generated to implement the  
23 specification, and

24 causing the code to be installed on the client.

1 12. (Currently amended) The computer-readable storage medium of  
2 claim 11, wherein causing the client to obtain the service profile involves:

3 causing the client to send a request for the service profile to the service  
4 provider of the new service; and

5 causing the client to receive the service profile from the service provider  
6 of the new service.

1           13.     (Original) The computer-readable storage medium of claim 11,  
2     wherein the service profile includes code, and wherein causing the service profile  
3     to be installed on the client involves causing the code to be installed on the client.

1           14.     (Cancelled)

1           15.     (Original) The computer-readable storage medium of claim 11,  
2     wherein the service profile is encoded in a universal form that can be executed by  
3     different types of clients.

1           16.     (Currently amended) The computer-readable storage medium of  
2     claim 11,  
3             wherein there exist different service profile implementations for different  
4     types of clients; and  
5             wherein causing the client to obtain the service profile involves,  
6                     communicating characteristics of the client to the service  
7                     provider of the new service,  
8                     allowing the service provider of the new service to select a  
9                     service profile implementation for the client based on the  
10                    characteristics of the client, and  
11                    allowing the service provider of the new service to send the  
12                    selected service profile implementation to the client.

1           17.     (Currently amended) The computer-readable storage medium of  
2     claim 11, wherein causing the client to obtain the service profile from the service  
3     provider of the new service involves executing a dynamic extension profile, which  
4     implements a standard protocol that enables the client to acquire any profile the  
5     client needs at the time the profile is needed.

1           18.     (Currently amended) The computer-readable storage medium of  
2     claim 11,  
3           wherein performing the discovery operation involves using the Bluetooth  
4     Service Discovery Protocol (SDP); and  
5           wherein the client and the service provider of the new service  
6     communicate using the Bluetooth networking standard.

1           19.     (Original) The computer-readable storage medium of claim 11,  
2     wherein the service profile can define a service-specific Application Programming  
3     Interface (API).

1           20.     (Original) The computer-readable storage medium of claim 11,  
2     wherein the service profile implements a domain-specific protocol stack  
3     associated with the new service.

1           21.     (Currently amended) An apparatus that facilitates dynamic delivery  
2     of service profiles to a client, comprising:  
3           a discovery mechanism configured to perform a discovery operation that  
4     allows the client to discover new services on a network;  
5           a profile transfer mechanism, wherein if a new service is discovered for  
6     which the client does not possess a service profile for the new service, the profile  
7     transfer mechanism is configured to cause the service profile to be transferred  
8     from a service provider of the new service to the client;  
9           wherein causing the client to obtain the service profile involves:  
10           causing the client to send a request for the service profile to the  
11           service provider of the new service, wherein the request includes type  
12           information identifying the type of device platform of the client; and

13 causing the service provider ~~new service~~ to select the service  
14 profile from a set of service profiles based on the received type  
15 information of the client; and  
16 an installation mechanism configured to cause the service profile to be  
17 installed on the client to enable the client to use the new service,  
18 wherein the service profile includes a specification that describes how to  
19 use the new service, and wherein the installation mechanism is configured to,  
20 cause device-specific code to be generated to implement the  
21 specification, and  
22 cause the code to be installed on the client.

1 22. (Currently amended) The apparatus of claim 21, wherein the  
2 profile transfer mechanism is configured to:  
3 cause the client to send a request for the service profile to the service  
4 provider of the new service; and to  
5 cause the client to receive the service profile from the service provider of  
6 the new service.

1 23. (Original) The apparatus of claim 21, wherein the service profile  
2 includes code, and wherein the installation mechanism is configured to cause the  
3 code to be installed on the client.

1 24. (Cancelled)

1 25. (Original) The apparatus of claim 21, wherein the service profile is  
2 encoded in a universal form that can be executed by different types of clients.

1 26. (Currently amended) The apparatus of claim 21,

2           wherein there exist different service profile implementations for different  
3 types of clients; and  
4           wherein the profile transfer mechanism is configured to,  
5                 communicate characteristics of the client to the service  
6                 provider of the new service,  
7                 allow the service provider of the new service to select a  
8                 service profile implementation for the client based on the  
9                 characteristics of the client, and to  
10                 allow the service provider of the new service to send the  
11                 selected service profile implementation to the client.

1           27.     (Original) The apparatus of claim 21, wherein the profile transfer  
2 mechanism is configured to execute a dynamic extension profile, which  
3 implements a standard protocol that enables the client to acquire any profile the  
4 client needs at the time the profile is needed.

1           28.     (Currently amended) The apparatus of claim 21,  
2 wherein the discovery mechanism uses the Bluetooth Service Discovery  
3 Protocol (SDP); and  
4           wherein the client and the service provider of the new service  
5 communicate using the Bluetooth networking standard.

1           29.     (Original) The apparatus of claim 21, wherein the service profile  
2 can define a service-specific Application Programming Interface (API).

1           30.     (Original) The apparatus of claim 21, wherein the service profile  
2 implements a domain-specific protocol stack associated with the new service.



1           31.     (Currently amended) A device configured to dynamically deliver a  
2     service profile to a client to enable the client to use a service provided by the  
3     device, comprising:

4                 the device configured to provide the service;  
5                 a memory within the device containing the service profile that enables  
6     clients to use the service provided by the device;

7                 a service profile obtaining mechanism configured to cause the client to  
8     obtain the service profile by:

9                     causing the client to send a request for the service profile to the  
10                    ~~device the new service~~, wherein the request includes type information  
11                    identifying the type of device platform of the client; and

12                    causing the ~~device new service~~ to select the service profile from a  
13                    set of service profiles based on the received type information of the client;  
14                    and

15                    a profile transfer mechanism configured on the device to transfer the  
16     service profile to the client on demand,

17                    wherein the service profile includes a specification that describes how to  
18     use the new service, and wherein causing the service profile to be installed on the  
19     client involves,

20                    causing device-specific code to be generated to implement the  
21                    specification, and

22                    causing the code to be installed on the client.

1           32.     (Original) The device of claim 31, further comprising a discovery  
2     mechanism configured to perform a discovery operation that allows devices to  
3     discover each other.